



HONDA Civic Type-R, FL5, 01/2023=>

2.01 VTEC Turbo 242 kW (K20C1, with GPF)

AVAILABLE FOR ORDER NOW (READY FOR DELIVERY IN CALENDAR WEEK 42)

HONDA Civic Type-R, FL5, 01/2023=> 2.01 VTEC Turbo 242 kW (K20C1, with GPF)

ABOUT

GPF-back-system centered: 257023 0300 + 257023 5500 + tail pipe set! No vehicle modifications are

required!

tem centered:

RACING-downpipe-back-sys- 257123 1200 (No EC type approval) + 257123 5500 (No EC type approval) + tail

pipe set! No vehicle modifications are required!

The use of racing products and products that do not have EC approval is not permitted on public roads.

When installing REMUS sports silencers, cat-back systems and cat replacement pipes designed for use on closed tracks, it is advantageous to carry out an ECU remapping in order to exploit the optimum performance of the exhaust system and to prevent any illumination of the engine control light.

257023 0300

GPF-back resonated front-section

only mountable in combination with REMUS sport exhaust 257023 5500

incl. mounting material

Connection to front parts at the manufacturer connection point

Installation/fitting at the serial mounting points Original tube Ø 60 mm - REMUS tube Ø 76 mm incl. EC type approval

257023 5500

Sport exhaust centered (absorption principle)

with one integrated valve (centered) incl connection tube

incl. mounting material

Installation/fitting at the serial mounting points The activation of the valve is carried out using the original actuator via the vehicle onboard electronics. Original tube Ø 60 mm - REMUS tube Ø 76 mm incl. EC type approval

257123 1200

Non-resonated RACING downpipe-back front-section

incl. front silencer replacement tube

only mountable in combination with REMUS sport exhaust 257123 5500

incl. mounting material

Connection to front parts at the manufacturer connection point

Installation/fitting at the serial mounting points Original tube Ø 60 mm - REMUS tube Ø 76 mm No EC type approval

257123 5500

Racing sport exhaust centered (absorption principle)

with one integrated valve (centered) incl connection tube

incl. mounting material

Installation/fitting at the serial mounting points The activation of the valve is carried out using the original actuator via the vehicle onboard electronics. Original tube Ø 60 mm - REMUS tube Ø 76 mm No EC type approval



0436 70SGR

Stainless steel tail pipe set

3 tail pipes Ø 102 mm angled (shorter length 145 mm), straight cut, chromed, with adjustable spherical clamp connection

255,·

0436 70SGBR

Stainless steel tail pipe set

3 tail pipes Ø 102 mm angled (shorter length 145 mm), straight cut, Black Chrome, with adjustable spherical clamp connection

306,-

0436 70CSR

Carbon tail pipe set

3 tail pipes Ø 102 mm angled (shorter length 145 mm), Titanium internals, with adjustable spherical clamp connection

726,-

ADOPT1S-3

OPT tail pipe adaptor

3-pcs-set, short incl. mounting material

39,-



0038 70TI

Titanium tail pipe set

3 tail pipes OPT OnePieceTechnology brushed (only fit together with ADOPT1S-3)

510,-



0038 70TIB

Titanium tail pipe set

3 tail pipes OPT OnePieceTechnology black coated (only fit together with ADOPT15-3)

624,-

THE SOUND OF CANADAS®

FIRST CLASS QUALITY DESIGNED & BUILT IN EUROPE | AUSTRIA

www.remus.eu

- remus.sportexhaust
- REMUS Innovation GmbH
 Ruhmannstraße 11
 A-8570 Voitsberg